

**Product data FASSON THERMAL 200LD S2000N-BG40BR**

No Imprint / **ANK686**  
EAN Code : 8712739341911  
Spec Code : AI667  
Issue date : 28-Apr-2010

**FaceStock**

A white, woodfree printing paper with a high sensitivity thermal coating providing good image resolution.

Basis Weight 75g/m<sup>2</sup> ISO 536

**Adhesive**

A general purpose permanent, acrylic based adhesive.

**Liner**

BG40 brown, a supercalendered glassine paper.

Basis Weight 59g/m<sup>2</sup> ISO 536

Caliper 0.053mm ISO 534

Transparency 50% ISO 2469

**Laminate**

Total Caliper 0.156mm +/- 10%

**PERFORMANCE DATA**

Initial Tack 500N/m FTM 9 glass  
Peel Adhes. 90° 300N/m FTM 2 st.st.

Min. appl. temp. 0 °C  
Service temp. -20 °C --> +70 °C

**Adhesive performance**

The adhesive is characterized by a high initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates.

The adhesive complies with the European food directives and legislations, FDA 175.105 and the German recommendations XIV as published by BfR (Bundesinstitut für Risikobewertung) is the German Federal Institute for Risk Assessment. The adhesive can be used in direct contact with dry, non fatty foodstuffs.

**Applications and use**

This Direct Thermal product is designed for use in dry weigh scale, process tracking, point of sale item information labelling where limited image durability is required. Typical end applications include fruit and vegetable weigh scale, hardware, work-in-process material tracking. Contact with moisture, oil, fats, plasticizers and exposure to strong lighting should be avoided due to potential image fade.

**Conversion / Printing**

This product is designed to be converted and dispensed at high speed by all conventional roll conversion technologies, including flexographic and UV letterpress. Due to the thermographic properties, exposure above 50°C may cause premature imaging or discoloration. Inks containing alcohol or volatile organic solvents may also cause discoloration. It is advisable to test inks and varnishes before conversion.

N.B. : We recommend not to pre-print the thermal imaged area with water based flexographic inks.

**Shelf life**

One year after manufacturing. Thermally printed labels are restricted to one year, both if stored at 22°C / 50% RH

N.B. : All data to be considered as typical values.



Avery Dennison Roll Materials Europe  
Lammenschansweg 140, P.O. Box 28  
NL - 2300 AA Leiden - The Netherlands  
Tel +31 71 5794100 - Fax +31 71 5794180  
<http://www.europe.fasson.com>

**Warranty**

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge or AVERY DENNISON may issue credit in such amount as it deems reasonable however, in no event shall AVERY DENNISON be responsible for claims beyond the

replacement value of the defective product or in any way liable or responsible for consequential or incidental damages.

NO EXPRESS WARRANTIES AND NO IMPLIED WARRANTIES, WHETHER OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE, OR OTHERWISE, EXCEPT AS SET FORTH ABOVE (WHICH IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES) SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON.

No salesman, representative, or agent of AVERY DENNISON is authorized to give any guarantee, warranty or make any representation contrary to the above.